#### **ENGINEERING CHANGE NOTICE**

Page 1 of <u>2</u>

1. ECN 612286

Proj. ECN

2. ECN Category (mark one)	<ol> <li>Originator's Name and Telephone No.</li> </ol>	e, Organization, MSIN,	4. USQ Required	?	5. Date
Supplemental (18 18) Direct Revision	B. C. Simpson, 373-5915		[] Yes [X]	No	7/10/97
Change ECN []	6. Project Title/No.	/Work Order No.	7. Bldg./Sys./Fa	ac. No.	8. Approval Designator
Temporary [] Standby []	Tank 2	241-C-203	NA NA		NA
Supersedure [] Cancel/Void []	9. Document Numbers (includes sheet n	Changed by this ECN	10. Related ECN	No(s).	11. Related PO No.
	<u>-</u>	R-478, Rev. OB	NA NA		NA
12a. Modification Work	12b. Work Package	12c. Modification Work			d to Original Condi- or Standby ECN only)
[] Yes (fill out Blk. 12b)	NA NA	NA	N/A	-	or standby Eth Onty)
[X] No (NA Blks. 12b, 12c, 12d)		Design Authority/Cog. Signature & Da			hority/Cog. Engineer mature & Date
13a. Description of Change Add Appendix A, Eva		blish Best-Basis I	nventory for	Single-	-Shell Tank
					·
14a. Justification (mark o	one)				
Criteria Change []	Design Improvement	[] Environmental	[]	Facility	Deactivation []
As-Found [X]	Facilitate Const	[] Const. Error/C	mission []	Design E	rror/Omission []
14b. Justification Details					
		vide waste invento			
standard character part of this effor					
241-C-203 was perfe					
the methodology th	at was establish	ed by the standard	l inventory t	ask.	
15. Distribution (include	name, MSIN. and no. o	f copies)		R	ELEASE STAMP
Central Files	43-88 K. M	l. Hall R2-1	.2		
		I. Hodgson		JG 20	100,00
	15-49	i. Connet RZ-1	. +	DATE:	HANFORD
B. C. Simpson	R2-12			STA: 37	
	15-49			OIN: 2	RELEASE 10:
M. D. LeClair (3)	1U-5U				~ (50)
• •					

ENGINEERING CHANGE NOTICE				Page 2 of 2	1	e no. from pg. 1)	
16. Design Verification Required	17. Cost Impact	: NEERING	CC	NSTRUC	TION	18. Schedule Im	pact (days)
[] Yes	Additional	Γ1 <b>\$</b>	Additional	ſ	] \$	Improvement	Γ٦
[X] No	Savings	[] \$	Savings	Ī	] \$	Delay	וֹן
19. Change Impact R that will be af	eview: Indicate fected by the ch	the related ange describ	documents (other t	han the ter the	engineering of	ocuments identifi ment number in Bl	ed on Side 1) ock 20.
SDD/DD	[]	Sei	smic/Stress Analysis		[]	Tank Calibration Mar	nual []
Functional Design Criteria	· []	Str	ess/Design Report		[ ]	Health Physics Proce	
Operating Specification	[]	Inte	erface Control Drawing		ĒĪ	Spares Multiple Unit	
Criticality Specification	[]	Cal	ibration Procedure			Test Procedures/Spe	
Conceptual Design Repor	t []	Inst	tallation Procedure		ĪĪ.	Component Index	[]
Equipment Spec.	ĨĨ	Mai	intenance Procedure		ĨĨ	ASME Coded Item	įj
Const. Spec.	ĨĨ	Eng	ineering Procedure		ΪĬ	Human Factor Consi	
Procurement Spec.	įί	Оре	erating Instruction		Ϊĺ	Computer Software	į̇̃
Vendor Information	īī	Оре	erating Procedure		ři	Electric Circuit Sche	
OM Manual	ίi	Оре	erational Safety Requirem	ent	[]	ICRS Procedure	
FSAR/SAR	• [ ]	IEFI	D Drawing		Ϊ	Procesș Control Man	
Safety Equipment List	Ϊĺ	Cell	Arrangement Drawing			Process Flow Chart	וֹז
Radiation Work Permit	- ii	Ess	ential Material Specificat	on	Γĺ	Purchase Requisition	ři
Environmental Impact Sta	tement	Fac	. Proc. Samp. Schedule		ří	Tickler File	ii
Environmental Report	וֹז	lns	ection Plan				[]
Environmental Permit	ָּהָי רוֹ	Inve	entory Adjustment Reque	st			[]
		E: Documents ization has b	s listed below will been notified of ot Document Number/Ra	ner aff	ected document	is ECN.) Signatum s listed below. Document Numbe	
21. Approvals		<del></del>					
21. Approvats	Signature		Doto		61		,
Design Authority	•		Date	Desig	ຈາງເ In Agent	nature	Date
Cog. Eng. M. J. Ku	ofer 25 Kay	2/	B ( 47	PE	_		
Cog. Mgr. K. M. Ho	dgson K.M. J	l.	8-14-97	QA			<del></del>
QA	- · · · · · · · · · · · · · · · · · · ·	wy -	0 (4-7)	Safet	: <b>y</b>		
Safety				Desig	•		<del></del>
Environ.				Envir	on.		. ——
Other J. M. Conner	MI Con		8-14-97	7 Other		-	<del></del> i
	M Com	<b>-</b>	<u> </u>				
				DEPAR	TMENT OF ENERG	Υ	<del></del> !
				Signa	iture or a Cont	rol Number that	
				track	s the Approval	o i gnature	
•				ADDIT	IONAL		<del></del>
			<del></del>				·
							<del></del>

### Tank Characterization Report for Single-Shell Tank 241-C-203

B. C. Simpson

Lockheed Martin Hanford Corporation, Richland, WA 99352 U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 612286

UC: 712

Org Code: 74610

Charge Code: N4G3A

B&R Code: EW3120074

Total Pages:

Key Words: TCR, best-basis inventory

Abstract: An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities. As part of this effort, an evaluation of available information for single-shell tank 241-C-203 was performed, and a best-basis inventory was established. This work follows the methodology that was established by the standard inventory task.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

HANFORD **新始 37** 

DATE

Retease Stamp....

# (1) Document Number **RECORD OF REVISION** WHC-SD-WM-ER-478 Page A (2) Title Tank Characterization Report for Single-Shell Tank 241-C-203 CHANGE CONTROL RECORD (3) Revision (4) Description of Change - Replace, Add, and Delete Pages

(3) NOVISION		(5) Cog. Engr.	(6) Cog. Mgr. Date
. 0	(7) Initially released 08/07/95 on EDT-612680.	J.A. Lechelt	J.G. Kristofzski
0-A RS	Incorporate per ECN-623847.	L.M. Sasaki Sim Sasaki	J.G. Kristofzski
		<u> </u>	
0-B <b>RS</b>	Incorporate per ECN-625684.	L.M., Sasaki	J.G. Kristofzski GAL-forsk 7/18
		<del>-  </del>	1/18/
OC RS	Incorporate per ECN-612286	M.J. Kupfer	K.M. Hodgson
		1000 Key 2 8-189;	K.M. Valgr 8/14/9
<u> </u>			
·			
		<del></del>	
· · · · · · · · · · · · · · · · · · ·			•
			•
<u>,, </u>			
	·		
·			
	<b>i</b>	1	1

## APPENDIX A

# EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR SINGLE-SHELL TANK 241-C-203

This page intentionally left blank.

#### APPENDIX A

# EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR SINGLE-SHELL TANK 241-C-203

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for single-shell tank 241-C-203 was performed, and a best-basis inventory was established. This work, detailed in the following sections, follows the methodology that was established by the standard inventory task. The following evaluation provides a best-basis inventory estimate for chemical and radionuclide components in tank 241-C-203.

#### A1.0 CHEMICAL INFORMATION SOURCES

Data sources for tank 241-C-203 include the following:

- Mean characterization results and inventory estimates from a core sample obtained in 1978 from tank 241-C-201 (Horton 1978). The sample had limited information collected from it, and no associated quality control assays; however, the principle assumption is that the C-200 series tanks contain basically the same waste types. Information for tank 241-C-201 serves as a basis for tank 241-C-203.
- Two auger samples were obtained from tank 241-C-103 for safety screening analysis in 1995 (Conner 1995); however, the data obtained did not contribute to the chemical information available.
- The Hanford Defined Waste (HDW) model (Agnew et al. 1997a) provides tank contents estimates, derived from process flowsheets and waste volume records.

#### A2.0 COMPARISON OF COMPONENT INVENTORY VALUES

The 1978 data-based inventory estimate for tank 241-C-201, adjusted to the volume of tank 241-C-203, and the 241-C-203 inventory estimate from the HDW model (Agnew et al. 1997a) are shown in Table A2-1 and A2-2. Each estimate, however, has a different density basis.

The HDW inventory estimates use a waste volume of 18.9 kL (5 kgal), and a waste density of 1.64 g/mL. The data-based inventory (using data from tank 241-C-201) uses a volume of 18.9 kL (5 kgal), and a measured bulk density of 1.16 g/mL as bases.

Measurements from the samples indicate that the density is approximately 1.62 g/mL. To maintain consistency in the data use, the density from tank 241-C-201 will be used in the base calculations. Because of the difference between the two estimates for the mass basis (relative percent difference = 34.3 percent), many differences between the sample-based and HDW model inventories are observed.

Estimates obtained from the two methods for most analytes vary by a factor of two or more. The chemical species in this section are reported without charge designation per the best-basis inventory convention.

Table A2-1. Sample and Hanford Defined Waste Model-Based Inventory Estimates for Nonradioactive Components in Tank 241-C-203.

Analyte	Data-based inventory estimate <sup>a</sup> (kg)	HDW model inventory estimate <sup>6</sup> (kg)	Analyte	Data-based inventory estimate* (kg)	HDW model inventory estimate <sup>b</sup> (kg)
Al	35.3	0	NO <sub>3</sub>	724	69.2
Bi	NR	0	OН	110°	3,940
Ca	NR	51.7	Pb	NR	119
Cl	44.0	6.17	PO <sub>4</sub>	3,250	575
Cr	2.95	2.37	Si	82.3	0.726
F	11.0	0	SO <sub>4</sub>	NR	151
Fe	1,362	1,300	Sr	NR	0
K	8.80	10.8	TIC as CO <sub>3</sub>	440	1,720
NH <sub>3</sub>	NR	16.2	TOC	45.5	76.9
Na	595	1,920	U <sub>TOTAL</sub>	1.46	6,310
Ni	176	41.7	Zr	NR	0
NO <sub>2</sub>	22.1	159	H <sub>2</sub> O (Wt%)	68.0	46.4
			Density (kg/L)	1.16	1.64

HDW = Hanford Defined Waste

NR = Not reported

<sup>&</sup>lt;sup>a</sup> Derived from data for tank 241-C-201 (Horton 1978) and adjusted to the volume of tank 241-C-203

<sup>&</sup>lt;sup>b</sup> Agnew et al. (1997a)

<sup>°</sup> Obtained from soluble portion only.

Table A2-2. Sample and Hanford Defined Waste Model-Based Inventory Estimates for Radioactive Components in Tank 241-C-203.

Analyte	Data-based inventory estimate <sup>a</sup> (Ci)	HDW model inventory estimate <sup>b</sup> (Ci)
<sup>137</sup> Cs	169	34.7
<sup>90</sup> Sr	900	30,700
<sup>239/240</sup> Pu	50	16.5
Total α	33.2°	NR

HDW = Hanford Defined Waste

NR = Not reported

#### A3.0 COMPONENT INVENTORY EVALUATION

The following evaluation of tank contents is performed in order to identify potential errors and/or missing information that would influence the sample-based and HDW model component inventories. The types and volumes of solids accumulated in tank 241-C-203 reported by various authors is compiled in Tables A3-1, A3-2, and A3-3.

#### A3.1 CONTRIBUTING WASTE TYPES

The process history documents indicate the tank received mostly metal waste (MW) and Hot Semiworks/Strontium Semiworks (HS/SSW) waste while the tank was active. Tank 241-C-203 went into service in 1947, receiving metal waste through a diversion box (Agnew et al. 1997b). Metal waste sludge, which originated from uranium fuel dissolution in the bismuth phosphate process, was then sluiced from waste storage tanks, and the uranium in the waste was separated from fission products using a solvent extraction process based on tri-butyl phosphate (TBP). Most of the metal waste was removed from the tank in 1954 during the uranium recovery campaign. For the remainder of its service life, from 1955 to 1976, tank 241-C-203 received and stored HS/SSW (Agnew et al. 1997b). Because of the supporting information from process history, for purposes of this evaluation, the tank inventory is considered to be entirely HS/SSW.

<sup>&</sup>lt;sup>a</sup> Derived from data for tank 241-C-201 (Horton 1978) and adjusted to the volume of tank 241-C-203

<sup>&</sup>lt;sup>b</sup> Agnew et al. (1997a)

<sup>&</sup>lt;sup>e</sup> Based on analyses of 1995 auger samples from tank 241-C-203 (Conner 1995).

Table A3-1. Waste Inventory of Tank 241-C-203 (Hanlon 1997).

Waste	Volume (kL)	Volume (kgal)
Sludge	18.9	. 5
Saltcake	0	0
Supernatant	0	0
Drainable Interstitial Liquid	0	0
Total Waste	18.9	5

Table A3-2. Expected Solids for Tank 241-C-203.

Reference	Waste Type
Anderson (1990)	MW, HS/SSW
SORWT Model (Hill et al. 1995)	HS/SSW
WSTRS (Agnew et al. 1997b)	MW, HS/SSW
HDW Model (Agnew et al. 1997a)	MW, HS/SSW

HDW = Hanford Defined Waste

HS/SSW = Hot Semiworks/Strontium Semiworks

MW = Metal waste

SORWT = Sort on radioactive waste type

WSTRS = Waste Status and Transaction Record Summary.

Table A3-3. Hanford Defined Waste Model Solids for Tank 241-C-203

HDW solids layer	kL	kgal
MW	15.1	4
HS/SSW	3.8	1
Total HDW Volume	18.9	5

HDW = Hanford Defined Waste, Agnew et al. (1997a)

HS/SSW = Hot Semiworks/Strontium Semiworks

MW = Metal waste.

#### A3.2 EVALUATION OF PROCESS FLOWSHEET INFORMATION

Tank 241-C-203 contains a small amount of sludge. Technical flowsheet information for the HS/SSW stream is provided in Table A3-4. The comparative HDW is also provided in this table. The purpose of the comparison is to evaluate the accuracy, completeness, and reliability of the historical data.

Table A3-4. Technical Flowsheet and Hanford Defined Waste Compositions.

Analyte	Flowsheet HS/SSW <sup>a</sup> (mol/L)	HDW <sup>b</sup> HS/SSW (mol/L)
Ba	2.0 E-04	NR
Ca	0.0049	0.0049
Fe	0.03	0.07
Се	0.0017	NR
Acetate	1.34	0.51
Κ.	0.078	0.089
Na	4.9	2.21
ОН	1.32	0.33
NO <sub>3</sub>	2.1	1.08
Pb	0.034	0.0034
Rare Earths	0.0069	NR
Sr	5.0 E-04	NR

HDW = Hanford Defined Waste

HS/SSW = Hot Semiworks/Strontium Semiworks

NR = Not reported

#### A3.3 ENGINEERING EVALUATION OF TANK SAMPLE INFORMATION

An estimate of the waste inventory in tank 241-C-203 will be derived using information independent from the composition information contained in Horton (1978).

<sup>&</sup>lt;sup>a</sup> Hill et al. (1995)

<sup>&</sup>lt;sup>b</sup> Agnew et al. (1997a).

#### A3.3.1 Hot Semiworks/Strontium Semiworks Composition Estimate

Table A3-5 provides an estimate of the waste composition in tank 241-C-203 using the waste composition from data extracted from the flowsheet. In-tank photographs of tank 241-C-203 (Section 2.0) show a cracked black surface with some bright yellow material. No apparent moisture and no standing liquid are observed. The current differential scan calorimetry thermogravimetric analysis (DSC/TGA) information provides percent water measurements of 31 to 51 percent.

Table A3-5 also shows data for tank 241-C-203 based on the 1978 sampling event of tank 241-C-201 (Horton 1978). The results are for a single composite. Sample recovery appears to have been average to poor and only one riser was sampled. The core sample analysis were not documented to current QC requirements; however, there is no reason to believe that the samples were not analyzed using good laboratory practice. The tank's process history, inspection of the available data, and visual observation of the current tank photos suggest that spatial heterogeneity may be significant for this tank.

The 1995 analysis was conducted on two auger samples. The results do not contain any relevant chemical species information, because only DSC/TGA, total organic carbon (TOC), and total alpha activity information was collected (Conner 1995).

#### A3.3.2 Basis For Sample Calculations Used In This Independent Evaluation

The total volume of waste that passed through these tanks is not well quantified and the amount of each contributing waste type is unknown. The HDW model inventory is based on assumptions regarding the physical behavior and composition of the waste types identified from process history, which have not been confirmed. This tank was recently sampled, but very little analytical data were collected. Thus, that sampling event is not useful in this process (Conner 1995). Although process information is not complete, Hill et al. (1995) gives a generalized flowsheet for HS/SSW waste which was used to estimate selected analyte inventories. Horton (1978) is used extensively as the sample-based estimate, and Hanlon (1997) provides the volume basis.

#### A3.3.3 Assumptions

The assumptions and observations are based upon best technical judgement pertaining to parameters that can significantly influence tank inventories. These parameters include: (1) correct predictions of contributing waste types, (2) accurate predictions of model flowsheet conditions, fuel processed, and waste volumes, (3) accurate predictions of component solubilities, and (4) accurate predictions of physical parameters such as density, percent solids, void fraction (porosity), etc.

As necessary, the assumptions used can be modified to provide a basis for identifying potential errors and/or missing information that could influence either or both data- and model-based inventories. The simplified assumptions and observations use for predicting the inventory of several analytes in tank 241-C-203 are as follows:

- 1. Only HS/SSW introduced into tank 241-C-203 contributed to solids formation.
- 2. Radiolysis of NO<sub>3</sub> to NO<sub>2</sub> and any addition of NO<sub>2</sub> to the waste in tank 241-C-203 for corrosion control purposes are not accounted for in this independent assessment.
- 3. All Ba, Ca, Ce, Fe, Pb, and Sr from the HS/SSW flowsheet precipitated.
- 4. The currently accepted surveillance volume, the sample data concentrations, and sample data derived density were used in calculating the data-based inventories. The surveillance volume, the flowsheet concentrations (and other data, such as heat load estimates and 1995 sample data), and sample-based density was used in calculating the engineering assessment-based inventories. The HDW model-based inventories used its internal reference bases.
- 5. All acetate, K, and NO<sub>3</sub> were dissolved in the interstitial liquid. Al, Cr, PO<sub>4</sub>, OH, and F partition between the liquid and solid phases.
- 6. Concentration of components in interstitial liquid is based on a void fraction of 0.82257 for HS/SSW. Those components were not lost with the evaporation of the supernatant and interstitial liquid.

Estimated component inventories from the evaluation of tank 241-C-201 (Schreiber et al. 1997) have been adjusted by a volume ratio to obtain an engineering evaluation-based inventory estimate for tank 241-C-203. This tank 241-C-203 engineering evaluation-based inventory estimate is compared with tank 241-C-201 data- and HDW-based inventories for selected components in Table A3-5. In addition to sample data, the engineering evaluation-based estimates also used surveillance data and data gathered from the 1995 sampling effort to derive estimates. The data-based estimates have been adjusted to reflect the actual density data from tank 241-C-203, rather than using the density from tank 241-C-201 as a basis. Observations regarding these inventories are noted by component in the following text.

Table A3-5. Comparison of Selected Component Inventory Estimates for Tank 241-C-203 Waste.

Component	Engineering evaluation <sup>a</sup> (MT)	1978 data-based <sup>b</sup> (MT)	HDW estimate <sup>c</sup> (MT)
Ва	0.0225	NR	NR
Ca	0.16	NR	0.0517
Ce	0.19	NR	NR
Acetate	1.23	NR	0.094
Fe	1.36	1.90	1.30
K	0.048	0.012	0.011
Na	2.38	0.831	1.92
NO <sub>3</sub>	2.03	1.02	0.069
Pb	5.725	NR	0.119
Sr	0.035	NR	0
H <sub>2</sub> O (percent)	38.7 <sup>d</sup>	68.0	46.0
Radionuclide (Ci)			
<sup>90</sup> Sr	9,320°	1,260	30,700
<sup>137</sup> Cs	NR	236	34.7
<sup>239/240</sup> Pu	46.3 <sup>f</sup>	0.07	16.5

HDW = Hanford Defined Waste

NR = Not reported

MT = Metric tons

#### A3.5 DOCUMENT ELEMENT BASIS

This section compares the data-based estimate, the engineering assessment, and the inventory estimate calculated by the HDW model for selected analytes. Many of the differences observed between the estimates can be attributed to the differences in their respective mass bases. In other cases, the source term for the analyte in the waste type does not appear to be accurately or completely described. Furthermore, the HDW assumes that

<sup>&</sup>lt;sup>a</sup> Schreiber et al. (1997)

<sup>&</sup>lt;sup>b</sup> Horton (1978) adjusted for tank 241-C-203; adjusted to 1.62 g/mL density

<sup>&</sup>lt;sup>c</sup> Agnew et al. (1997a)

<sup>&</sup>lt;sup>d</sup> Based on thermogravimetric analyses for the 1995 auger samples (Conner 1995)

e Based on tank heat load (Kummerer 1995)

f Based on total alpha analyses for the 1995 auger samples (Conner 1995).

most of the waste in the tank is MW, rather than HS/SSW, resulting in discrepancies. Several analytes such as aluminum, bismuth, chloride, chromium, fluoride, potassium, silicon, zirconium, and uranium are not principal process chemicals in the HS/SSW waste and are not expected to be present.

**Barium.** No comparison with the other estimation methods is possible because barium is not tracked by Agnew et al. (1997a), or reported in the 1978 sample data (Horton 1978). There is a trace amount of barium in this tank.

Nitrate. Wide variation is observed between the three estimates. The engineering evaluation is four times as large as the data-based estimate, and both of these estimates are substantially larger than the HDW estimate. The reason for the disagreement between the HDW estimate and the other two methods is not clear; however, it is probably the result of a source term discrepancy.

Calcium. The HDW estimated inventory is smaller than the engineering estimate; however, both indicate that calcium is a relatively small contributors to the waste.

Cerium. No comparison with the other estimation methods is possible because cerium is not tracked by Agnew et al. (1997a), or reported in the 1978 sample data (Horton 1978). Based on the assumption that all of the cerium from the HS/SSW flowsheet precipitated, there is a trace amount of cerium in this tank.

Acetate. Wide variation is observed between the estimates. The engineering evaluation is approximately 13 times larger than the HDW model estimate. Current sample data from TOC and DSC results support a relatively high energetic organic content.

Iron. Modest variation is observed between the three estimates. The HDW estimated inventory is 33 percent smaller than the flowsheet evaluation. Because of the dependence of the concentration factor on iron sample and flowsheet data, there is no discrepancy between the engineering evaluation and sample data derived estimates.

**Sodium.** Extreme variation is observed between the three estimates. The difference between the extreme values is approximately a factor of four.

Total Hydroxide. Once the best-basis inventories were determined, the hydroxide inventory was calculated by performing a charge balance with the valences of other analytes. In some cases, this approach requires that other analyte (e.g., sodium or nitrate) inventories be adjusted to achieve the charge balance. During such adjustments, the number of significant figures is not increased. This charge balance approach is consistent with that used by Agnew et al. (1997b).

Lead. Wide variation is observed between the two estimates. No sample data estimate is available. The HDW estimated inventory is almost 50 times smaller than the engineering evaluation. Much of this discrepancy is attributable to the order of magnitude difference between the engineering evaluation and HDW flowsheet concentrations. The flowsheet composition supports a modest to high amount of lead in the waste.

Strontium. No comparison with the other estimation methods is possible. Non-radioactive strontium is considered to be zero in Agnew et al. (1997b), and it is not reported in the 1978 sample data (Horton 1978). There is a trace amount of strontium in this tank.

Water. Wide variation is observed between the three estimates. The HDW estimated inventory and engineering evaluation estimate are relatively close. Furthermore, the current sample data and tank observations support a water content for the tank that is consistent with those estimates. The tank has dried over time, thus most of the water and other volatiles have been lost. Any partially or totally soluble analytes that were dissolved in the interstitial liquid have precipitated and are part of the waste solids.

Strontium-90. Wide variation is observed between the three estimates. The HDW estimated inventory is over three times as large as the engineering evaluation, based on the heat load in the tank derived from its dome temperature (Kummerer 1995). The engineering estimate is 8 times larger than the data-based estimate. Current sample data appear to be biased low because of waste heterogeneity.

Cesium-137. Wide variation is observed between the two estimates. No basis for an engineering estimate is available. The HDW estimated inventory is approximately 15 percent of the data-based estimate. The sample data supports a modest amount of <sup>137</sup>Cs in the waste.

Total Alpha/Plutonium-239/240. Wide variation is observed between the three estimates. The 1978 data-based estimate provides an extremely low value, over 2 orders of magnitude smaller than the HDW estimate. The HDW estimated inventory is almost 3 times smaller than the 1995 sample-based estimate. The 1995 sample data supports a relatively high inventory of an alpha emitter in the waste. This alpha emitter is conservatively assumed to be <sup>239/240</sup>Pu; however, there is no quantitative measurement of any of the individual alpha emitters.

#### A4.0 DEFINE THE BEST-BASIS AND ESTABLISH COMPONENT INVENTORIES

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of chemical information for tank 241-C-203 was performed, and a best-basis inventory was established. This work follows the methodology that was established by the standard inventory task.

The results from this evaluation support using the sample data-derived evaluation where possible as the best-basis value for tank 241-C-203 in most cases. However, because of the limited amount of data from both the samples and process history, the observed heterogeneity of the sample, and the wide variations in estimates that were derived from the three methods, there is no best source of estimates.

Best-basis inventory estimates for tank 241-C-203 are presented in Tables A4-1 and A4-2. The projected inventory is primarily based on a data-based evaluation of the tank; however, engineering estimates and HDW model values have been presented because of the incompleteness in the data. Engineering estimate values and data-based values are both designated "E" in Table A-1. The radionuclide inventories shown in Table A4-2 are based on the 1978 core sample results decayed to January 1, 1994, and Agnew et al. (1997b) HDW model estimates.

The inventory values reported in Tables A4-1 and A4-2 are subject to change. Refer to the Tank Characterization Database (TCD) for the most current inventory values.

Best-basis tank inventory values are derived for 46 key radionuclides (as defined in Section 3.1 of Kupfer et al. 1997), all decayed to a common report date of January 1, 1994. Often, waste sample analyses have only reported <sup>90</sup>Sr, <sup>137</sup>Cs, <sup>239/240</sup>Pu, and total uranium, or less frequently, total beta and total alpha, while other key radionuclides such as <sup>60</sup>Co, <sup>99</sup>Tc, <sup>129</sup>I, <sup>154</sup>Eu, <sup>155</sup>Eu, and <sup>241</sup>Am, etc., have been infrequently reported. For this reason it has been necessary to derive most of the 46 key radionuclides by computer models. These models estimate radionuclide activity in batches of reactor fuel, account for the split of radionuclides to various separations plant waste streams, and track their movement with tank waste transactions.

These computer models are described in Kupfer et al. (1997), Section 6.1, and in Watrous and Wootan (1997). Model generated values for radionuclides in any of 177 tanks are reported in the HDW Rev. 4 model results (Agnew et al. 1997a). The best-basis value for any one analyte may be either a model result or a sample or engineering assessment-based result if available. No attempt has been made to ratio or normalize model results for all 46 radionuclides when values for measured radionuclides disagree with the model. For a discussion of typical error between model derived values and sample-derived values, see Kupfer et al. (1997), Section 6.1.10.

Table A4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-C-203 (Effective May 31, 1997). (2 Sheets)

	Total		51, 1997). (2 bileous)
Analyte	inventory (kg)	Basis (S, M, E or C) <sup>1</sup>	Comment
Al	49	Е	Adjusted for density = 1.62 g/mL
Bi	0	M	
Ca	160	Е	·
Cl	61.4	E	Adjusted for density = 1.62 g/mL
TIC as CO <sub>3</sub>	614	Е	Adjusted for density = 1.62 g/mL
Cr	4.12	E	Adjusted for density = 1.62 g/mL
F	15.4	E	Adjusted for density = 1.62 g/mL
Fe	1,900	E	Adjusted for density = 1.62 g/mL
Hg	0	M	
. K	.11	M	
La	0	М	
Mn	0	M	
Na	1,920	M	Charge balance requirement
Ni	246	Е	Adjusted for density = 1.62 g/mL
NO <sub>2</sub>	30.9	E .	Adjusted for density = 1.62 g/mL
NO <sub>3</sub>	1,020	Е	Adjusted for density = 1.62 g/mL
ОН	1,150	С	
Pb	5,720	E	
PO <sub>4</sub>	4,500	Е	Adjusted for density = 1.62 g/mL
Si	115	Е	Adjusted for density = 1.62 g/mL
SO <sub>4</sub>	151	М	
Sr	0 -	М	
TOC	63.5	Е	Adjusted for density = 1.62 g/mL
U <sub>TOTAL</sub>	2.04	Е	Adjusted for density = 1.62 g/mL

Table A4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-C-203 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (kg)	Basis (S, M, E or C) <sup>1</sup>	Comment
Zr	0	M	

 $^{1}S = Sample-based$ 

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based or data-based

C = Calculated by charge balance; includes oxides as hydroxides, not including  $CO_3$ ,  $NO_2$ ,  $NO_3$ ,  $PO_4$ ,  $SO_4$ , and  $SiO_3$ .

Table A4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-C-203, Decayed to January 1, 1994 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E) <sup>1</sup>	Comment
<sup>3</sup> H	0.0152	M	
<sup>14</sup> C	0.0424	M	
<sup>59</sup> Ni	0.424	M	·
<sup>63</sup> Ni	41.5	M	
<sup>60</sup> Co	0.00196	M	·
<sup>79</sup> Se	0.00601	M	
90Sr	9,320	Е	From estimate of 1994-95 heat load
<sup>90</sup> Y	9,320	E	Based on <sup>90</sup> Sr
<sup>93</sup> Zr	0.0269	M	
<sup>93m</sup> Nb	0.0228	. M	
<sup>99</sup> Tc	0.0433	M	
<sup>106</sup> Ru	9.40 E-06	M	
<sup>113m</sup> Cd	0.0665	M	
<sup>125</sup> Sb	0.00495	M	
<sup>126</sup> Sn	0.00947	M	
<sup>129</sup> I	8.12 E-05	M	
<sup>134</sup> Cs	4.82 E-06	M	
<sup>137</sup> Cs	149	Е	Adjusted for density = 1.62 g/mL; 1978 sample data = 236 Ci
<sup>137m</sup> Ba	141	Е	Based on <sup>137</sup> Cs
<sup>151</sup> Sm	22.6	М	
<sup>152</sup> Eu	0.326	M	
<sup>154</sup> Eu	0.198	M	
155 Eu	21.3	M	
<sup>226</sup> Ra	3.88 E-05	М	
<sup>227</sup> Ac	1.85 E-04	М	MATERIAL
<sup>228</sup> Ra	2.19 E-10	M	
<sup>229</sup> Th	3.97 E-08	M	

Table A4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-C-203, Decayed to January 1, 1994 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E) <sup>1</sup>	Comment
<sup>231</sup> Pa	9.67 E-06	M	
<sup>232</sup> Th	1.86 E-12	M	
<sup>232</sup> U	2.47 E-05	M	
233U	1.48 E-06	M	
<sup>234</sup> U	2.08	M	
<sup>235</sup> U	0.0936	M	
236U	0.0133	M	
<sup>237</sup> Np	2.36 E-04	M	
<sup>238</sup> Pu	0.335	M	
<sup>238</sup> U	2.11	M	
<sup>239/240</sup> Pu	46.3	Е	From 1995 total alpha data
<sup>241</sup> Am	4.78	M	
<sup>241</sup> Pu	24.2	M	
<sup>242</sup> Cm	0.00769	M	
<sup>242</sup> Pu	1.19 E-04	M	
<sup>243</sup> Am	1.15 E-04	. M	
<sup>243</sup> Cm	4.22 E-04	M	
<sup>244</sup> Cm	2.05 E-04	M	

<sup>&</sup>lt;sup>1</sup>S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based.

This page intentionally left blank.

#### A5.0 APPENDIX A REFERENCES

- Agnew, S. F., J. Boyer, R. A. Corbin, T B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997a, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev. 4*, LA-UR-96-3860, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Agnew, S. F., R. A. Corbin, T. B. Duran, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997b, Waste Status and Transaction Record Summary (WSTRS Rev. 4), LA-UR-97-311 Rev. 0, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Anderson, J. D., 1990, A History of the 200 Area Farms, WHC-MR-0132, Westinghouse Hanford Company, Richland, Washington.
- Conner, J. M., 1995, 45-Day Safety Screen Results and Final Report for Tank 241-C-203, Auger Samples 95-AUG-020 and 95-AUG-021, WHC-SD-WM-DP-112, Rev. 0, Westinghouse Hanford Company, Richland, Washington
- Hanlon, B. M., 1996, Waste Tank Summary Report for Month Ending June 30, 1996, WHC-EP-0182-99, Westinghouse Hanford Company, Richland, Washington.
- Hill, J. G., G. S. Anderson, and B. C. Simpson, 1995, The Sort On Radioactive Waste Type Model: A Method to Sort Single-Shell Tanks into Characteristic Groups, PNL-9814, Rev. 2, Pacific Northwest Laboratory, Richland, Washington.
- Hodgson, K. M. and M. D. LeClair, 1996, Work Plan for Defining a Standard Inventory Estimate for Wastes Stored in Hanford Site Underground Tanks, WHC-SD-WM-WP-311, Rev. 1, Lockheed Martin Hanford Corporation, Richland, Washington.
- Horton, J. E., 1978, Analysis of Tanks 011-BXR, 201-C, and 204-T, (Letter Report to J. E. Mirabella, 60120-78-132J, dated December 4), Rockwell Hanford Operations, Richland, Washington.
- Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, B. C. Simpson, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W<sup>2</sup>S Corporation), 1997, Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

- Kummerer, M., 1995, Topical Report on Heat Removal Characteristics of Waste Storage Tanks, WHC-SD-WM-SARR-010, Rev. 1, Westinghouse Hanford Company, Richland, Washington.
- Schreiber, R. D., B. C. Simpson, C. S. Homi, and T. T. Tran, 1997, *Tank Characterization Report for Single-Shell Tank 241-C-201*, WHC-SD-WM-ER-476, Rev. 0C, Lockheed Martin Hanford Company, Richland, Washington.
- Watrous, R. A., and D. W. Wootan, 1997, Activity of Fuel Batches Processed Through Hanford Separations Plants, 1944 Through 1989, HNF-SD-WM-TI-794, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.